

HPURE BRAKE FLUID DOT 4

Product Description

Glycol Brake Fluid DOT 4 is engineered for all disc and drum type brake systems which call for DOT 4 or DOT 3 performance. It is formulated using a high quality glycol and glycol ether fluid. United Glycol Brake Fluid DOT 4 is formulated to tolerate extreme temperature conditions, which greatly reduces the tendency to vaporize at elevated temperatures, a common phenomenon in modern braking systems. This increased boiling resistance provides an extra margin of safety over conventional brake fluids.

This product is a highly stable product and maintains its superior protective qualities over long service and extreme conditions. This fluid functions consistently, whether the vehicle is operating in bitter, arctic cold or extreme desert heat. In addition, this product exhibits excellent lubricity and corrosion control and is safe for all materials used in vehicle braking systems.

Applications / Benefits

- Y Safe to mix with conventional brake fluids
- Y All season protection
- Y High and low viscosity control
- Y Compatible with rubber components

Typical Characteristics

Test Description	Method	Unit	
Equilibrium Reflux Boiling Point	FMVSS-116	-	270
Wet E.R. Boiling Point	FMVSS-116	-	165
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	1150
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	2
Effect on brake cups @ 70°C	FMVSS-116	-	NIL
Effect on rubber @ 120°C	FMVSS-116	-	NIL
Specific Gravity @ 15°C	ASTM D 4052	-	1.109
Color	-	-	Neutral

Reference No. BFDOT4REV0

Last revised date: 5/2/2024

www.hpure-lube.com

Issued by HPURE Lubricants Tel:(65) 6861 1157

Furnishing the information contained herein does not constitute a representation by HPURE Lubricants that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any third party. HPURE Lubricants assumes no liability for any infringement which might arise out the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. HPURE Lubricants warranty only that its products meet the specifications which it specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrantied of MERCHANTABILTY and FITNESS.