



Product Data Sheet

PLUTUS GX COMPRESSOR OIL

Product Description:

Plutus GX Compressor Oil is a premium performance, fully synthetic compressor oil based on polyalphaolefin and alkylated naphthalene technology. It contains a rust and oxidation inhibitor system plus anti-wear additives to provide outstanding oxidation resistance and corrosion protection. High viscosity index and low pour points of the polyalphaolefin base fluid permits application in a wider range of ambient operating temperatures than with conventional lubricants. Plutus GX Compressor Oil provides long oil life and effective lubrication in severe applications.

Plutus GX Compressor Oil is recommended for lubrication of reciprocating, rotary screw slide vane air compressors where the air delivery temperatures are greater than 150°C. But not recommended for use in breathing air compressors.

Applications / Benefits:

- ▣ Very good surface properties, rusting and wear protection
- ▣ Excellent thermal stability and outstanding resistance to oxidation.
- ▣ Extended oil service life. Minimum maintenance and downtime.
- ▣ High viscosity index and low pour point.
- ▣ Will allow the oils drain interval up to 8000* hours with normal operating temperature.

Typical Characteristics:

Test Description	Method	32	46	68	100	150
ISO Viscosity Grade	-					
Specific Gravity @ 15 °C	ASTM D 4052	0.838	0.842	0.846	0.847	0.850
Flash Point, °C	ASTM D 92	238	242	254	258	260
Pour Point, °C	ASTM D 97	-48	-45	-42	-42	-39
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	31.1	45.8	68.5	101	151
cSt @ 100°C	ASTM D 445	5.75	7.56	10.3	14.2	19.3
Viscosity Index	ASTM D 2270	128	131	136	144	146
Color	ASTM D 1500	<0.5	<0.5	<0.5	<0.5	<0.5

*Service hours values may differ according to operating parameters and temperatures, including maintenance status of the compressor.

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.