



PLUTUS SYN COMPRESSOR OIL

Product Description:

Plutus Syn Compressor Oil is designed for use in air compressors and high temperature circulating systems where freedom from deposit formation and extra long drain interval are desired. Formulated from tailor made fully synthetic base stocks and reinforced with carefully selected additives, Plutus Syn Compressor Oil is resistant to oxidation at all operating temperatures, thereby minimizing the formation of acidic oxidation products that can lead to system corrosion and reduced oil life. The naturally extra high viscosity index and provide stable viscosity characteristics and maintenance of a tough fluid film, even at high operating temperatures.

Applications / Benefits:

- ▣ Effective anti-oxidation action.
- ▣ Minimizes deposit formation.
- ▣ Superior anti-wear properties.
- ▣ Outstanding anti-rust and corrosion properties.
- ▣ Widest usable temperature range.
- ▣ Will allow the oils drain interval up to 6000* hours with normal operating temperature.

Typical Characteristics:

Test Description	Method	22	32	46	68	100	150
ISO Viscosity Grade	-						
Specific Gravity @ 15 °C	ASTM D 4052	0.841	0.843	0.848	0.852	0.857	0.861
Flash Point, °C	ASTM D 92	218	228	232	238	245	254
Pour Point, °C	ASTM D 97	-24	-21	-18	-18	-15	-15
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	22.2	30.5	44.2	68.2	99.8	150
cSt @ 100°C	ASTM D 445	4.57	5.62	7.30	9.91	13.13	17.7
Viscosity Index	ASTM D 2270	122	125	127	128	129	130
Color	ASTM D 1500	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5

Specifications, Approvals & Recommendations:

- DIN 51506 VDL specifications
- Suitable for following type of compressors: (1) Screw Compressor; (2) Piston and Reciprocating Compressor; (3) Vacuum Pump Compressor; (4) Airman; and (5) Other Japanese Brand Compressor.

*Service hours values may differ according to operating parameters and temperatures, including maintenance status of the compressor.

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.