

URE Product Data Sheet

PLUTUS SYN VACUUM PUMP OIL

Product Description:

Plutus Syn Vacuum Pump Oils are formulated from synthetic base stocks and specially selected additives designed to achieve premium performance that is suitable for each kind of mechanical vacuum pump, particularly in the areas of good oil-water separation property, resistance to wear and oxidized stability, high viscosity index and long life service.

Plutus Syn Vacuum Pump Oils have very narrow boiling spread and low volatility. As well as very low saturated steam pressure under the high temperature that guaranteed to obtain the high vacuum pressure.

Applications / Benefits:

- I Very low saturated steam pressure
- I High viscosity index
- I Resistance to wear protect.
- Outstanding long-term oxidation stability
- I Unsurpassed water separation properties

Typical Characteristics:

Test Description	Method					
ISO Viscosity Grade	-	32	46	68	100	150
Specific Gravity @ 15 °C	ASTM D 4052	0.856	0.865	0.870	0.874	0.885
Flash Point, °C	ASTM D 92	225	238	245	255	260
Pour Point , °C	ASTM D 97	-21	-21	-18	-18	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	32	46	68	100	150
cSt @ 100°C	ASTM D 445	5.86	7.42	9.35	12.0	15.5
Viscosity Index	ASTM D 2270	128	125	115	110	105
Color	ASTM D 1500	<0.5	<0.5	<1.0	<1.5	<2.0

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3'4 party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3'4 party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EVPRESS or IMPLIED