

Product Data Sheet

EST CHAIN OIL

Product Description:

EST Chain Oil is specially formulated with fully synthetic ester base oil that enables it to provide excellent lubricating properties even at very high temperatures. It provides maximum operating reliability with the optimum wear & oxidation protection.

EST Chain Oil essentially has a very high flash point that minimizes any fire hazard. Its very low volatility characteristic also enables less oil consumption and minimal deposit formation that leaves no harmful carbon deposit behind. Its unique formulation provides good adhesiveness even at escalated temperatures and also protects the metal surface from corrosion and rust.

EST Chain oil can be used in systems with operating temperatures as high as 250 °C while ensuring high operating reliability and low maintenance expenses on the conveyor system. Its extremely low pour point properties also makes it suitable for use in low temperature work environments such as cold rooms.

Applications / Benefits:

- I Excellent thermo-stability.
- I Forms no carbon deposit.
- I Excellent adhesiveness.
- I Good protection against rust and corrosion.

Typical Characteristics:

Test Description	Method					
ISO Viscosity Grade	-	100	150	220	320	460
Specific Gravity @ 15 °C	ASTM D 4052	0.958	0.967	0.978	0.981	0.905
Flash Point, °C	ASTM D 92	258	260	265	267	260
Pour Point, °C	ASTM D 97	-36	-33	-33	-30	-27
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	105	150	220	322	465
cSt @ 100°C	ASTM D 445	10.9	15.1	20.9	28.5	37.2
Viscosity Index	ASTM D 2270	85	100	112	120	122
Color	ASTM D 1500	<1.0	<1.0	<1.0	1.0	<1.5

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED