

# RE Product Data Sheet

# FTR LPG SUPER 4T

# **Product Description:**

FTR LPG Super 4T is a multi-function lubricant designed specially for vehicles burning gas as the fuel. It contains a balanced blend of select high performance, high viscosity index hydrocracked base stocks and a special proprietary anti-oxidation additive package that ensure it works perfectly in the usually red hot gas engine because of burning fuel gas.

#### Applications / Benefits:

- I Reduces engine wear and extends engine life.
- <sup>I</sup> Protects engine under high temperature operating conditions.
- I Retards harmful deposit formation on vital engine parts.
- Derotects against rust and corrosion.

# Typical Characteristics:

Method	
SAE J 300	20W50
ASTM D 4052	0.875
ASTM D 92	232
ASTM D 97	-18
ASTM D 445	192.2
ASTM D 445	20.5
ASTM D 2270	124
ASTM D 2896	6.1
ASTM D 1500	2.5
	SAE J 300 ASTM D 4052 ASTM D 92 ASTM D 97 ASTM D 445 ASTM D 445 ASTM D 2270 ASTM D 2896

# Suggested for the following uses:

- API SL
- JASO MA

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3'4 party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3'4 party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED