



Product Data Sheet

AUTOTRONIC ATF 7

Product Description:

Autotronic ATF 7 is a premium synthetic automatic transmission fluid. It is formulated with selected synthetic base stocks and latest additive technology available that provides excellent service in applications calling for low viscosity ATF, such as: Toyota Type WS, Nissan Matic S and Hyundai SP-IV.

Synthetic base stocks and stability of Autotronic ATF 7 protects against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -45° C. Moreover, it improves overall transmission durability and cleanliness.

Applications / Benefits:

- ▣ Provides excellent oxidation and thermal stability for longer life.
- ▣ Superior wear protection to protect critical transmission components.
- ▣ Excellent viscosity stability (high VI), application in low viscosity Auto Transmission.
- ▣ Much enhanced fluidity at very low temperature.
- ▣ Excellent rust and corrosion protection.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.845
Flash Point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	26.72
cSt @ 100°C	ASTM D 445	5.66
Viscosity Index	ASTM D 2270	160
Appearance	Visual	Red

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.



Product Data Sheet

Suggested for the following uses:

• Mazda FZ	SFU
• GM / GMC / Opel / Saturn AW1	SFU
• GM / GMC / Opel / Saturn VI	SFU
• Mitsubishi ATF-J3	SFU
• GM / GMC / Opel / Saturn P/N 88863400	SFU
• GM / GMC / Opel / Saturn P/N 88863401	SFU
• Nissan / Infinity Matic-S	SFU
• Honda / Acura DW-1	SFU
• BMW / MINI P/N 83 22 0 397 114	SFU
• Saab P/N 93 165 147 - AW-1	SFU
• Hyundai / Kia NWS-9638 T-5	SFU
• Hyundai / Kia SP-IV/SPH-IV	SFU
• Hyundai SP4-M (6-speed ATF)	SFU
• Toyota / Lexus / Scion Type WS	SFU
• Chrysler / Dodge / Jeep P/N 68043742AA	SFU
• Volkswagen / Audi G 055 540 (A2)	SFU
• Volkswagen / Audi G 060162 A1/A2/A6	SFU
• Ford / Lincoln / Mercury P/N XT-10-QLV [LV]	SFU
• Land rover P/N LR023288	SFU
• ZF Lifeguardfluid 8	SFU
• ATF Shell 3353	SFU
• ATF Shell 134	SFU
• ATF Shell M-1375.4	SFU
• Porsche P/N 000 043 304 00	SFU
• Mercedes / Daimler MB 236.12/14/15/41	SFU
• Jaguar 02JDE 26444	SFU
• Maserati P/N 231603	SFU

SFU = Suitable for Use

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.