

HPURE AUTOTRONIC CVTF LV

Product Description

Continuously Variable Transmission Fluid blended from high-performance fully synthetic base oils and carefully selected additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.

This oil is an automatic transmission well-balanced fluid specially designed for use in latest generations of Continuously Variable Transmissions (CVT) which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance of CVTs as compared with the regular automatic transmissions, many car makers have been adopting CVTs in more and more models.

Applications / Benefits

- ✓ Excellent low temperature fluidity, reducing start up wear
- ✓ Provides excellent friction, oxidation and thermal stability
- ✓ Outstanding anti-wear properties and oil film thickness
- ✓ Compatible with a wide range of seals

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8385
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.18
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.201
Viscosity Index	ASTM D 2270	-	201
Appearance	Visual	-	Green

Specifications, Approvals & Recommendations

Y AUDI/ VW	P/N G 052 180 (-A2)
Y AUDI/ VW	P/N G 052 516 A2
Y BMW/ MINI/ PUNCH	EZL 799
Y BMW/ MINI/ PUNCH	EZL 799A
Y BMW	P/N 83 22 0 136 376
Y BMW	P/N 83 22 0 429 154
Y CHERY	CVTF WCF-1
Y CHRYSLER / FCA	MOPAR CVTF+4 P/N 05191184A
Y DAIHATSU	AMMIX CVTF- DFE
Y DAIHATSU	AMMIX CVTF- DTC
Y DODGE/ JEEP	NS-2
Y FCA	CVTF+4 P/N 05191184AA
Y FORD	CFT23
Y FORD	CFT30
Y FORD	MERC C
Y FORD	WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
Y GM	CVTF I-GREEN2
Y GM	CVT P/N 19260800
Y GM	DEX-CVT
Y GM	HP-CVT P/N19355873
Y HONDA	CVTF P/N 08200-9006
Y HONDA	HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
Y HONDA	HCF-2 P/N 08200-HCF2
Y HYUNDAI / KIA	SP-CVT 1
Y IDEMITSU	CVTF-EX1
Y MAZDA	CVTF 3320
Y MINI COOPER	ZF CVT V1
Y MITSUBISHI	DIAMOND GREEN CVTF-J1
Y MITSUBISHI	DIAMOND GREEN CVTF-J4
Y NISSAN	NS-1
Y NISSAN	NS-2
Y NISSAN	NS-3
Y PROTON	PUNCH CVT; CVTF EX-1 (SFU)
Y RENAULT	ELFMATIC
Y SATURN	P/N 22688912
Y SHELL	GREEN 1V
Y SUBARU	LINEARTRONIC CVTF
Y SUBARU	LINEARTRONIC CVTF-II; P/N K0425Y0711
Y SUBARU	LINEARTRONIC CV-30 P/N K0425Y0710
Y SUBARU	e-CVTF
Y SUBARU	i-CVTF
Y SUBARU	HIGH TORQUE P/N K0421Y0700

Specifications, Approvals & Recommendations

Y SUZUKI	CVT FLUID GREEN 1
Y SUZUKI	CVT FLUID GREEN 2
Y SUZUKI	CVTF 3320
Y SUZUKI	NS-2
Y TOYOTA / LEXUS	FE
Y TOYOTA / LEXUS	TC

Reference No.
5800G3LONS3REV3

Last revised date:
19-05-25