

# HPURE FTR SCOOTER MATIC RACE 4T

## Product Description

**Fully Synthetic motorcycle oil tailored-made as a high-performance product to meet the unique demands of 4 stroke motorcycles. It not only lubricates critical engine components, but also provides protection for clutch assemblies and gearboxes.**

This product is formulated with the right combination and balance of components to combat undesirable potential issues such as gear pitting, clutch slip and higher levels of engine deposits. These advanced motorcycle oils are designed to deliver exceptional control from wear, corrosion and deposit formation as well as improved oxidative and thermal stability.

Providing unsurpassed clutch performance and friction durability throughout the oil life, this results in smoother operations and extended engine life with a more consistent and enjoyable overall riding experience.

## Applications / Benefits

- ✓ Protects engine under severe operating conditions
- ✓ Enhanced piston and engine cleanliness
- ✓ Retards harmful deposit formation on vital engine parts
- ✓ Provide clutch friction durability

## Typical Characteristics

Test Description	Method	Unit		
SAE Viscosity Grade	SAE J 300	-	<b>5W40</b>	<b>10W40</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.852	0.857
Flash Point	ASTM D 92	°C	216	228
Pour Point	ASTM D 97	°C	-39	-36
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	85.94	94.57
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.46	14.77
Viscosity Index	ASTM D 2270	-	176	163
TBN	ASTM D 2896	mgKOH/g	6.9	6.9
CCS	ASTM D 5293	cP	≤6600	≤7000

## Specifications, Approvals & Recommendations

---

Y	API	SP
Y	JASO	MB

Reference No.  
6120G3SPMBREV0

Last revised date:  
19/2/2024