



## **HPURE GLYCOL COOLANT**

## **Product Description**

Glycol Coolant provides excellent protection of the cooling system under extremes of cold weather. It protects all common cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This formulation is compatible with all other major brands of antifreeze and will not affect automotive hoses and gaskets.

This product is recommended for automotives and trucks cooling systems. Used in its neat form, it will act to prevent the cooling system from freezing over up to temperatures as low as  $-45^{\circ}$ C. This product is also suitable for heavy-duty use such as for diesel generators and off-road vehicles/ equipments.

This is recommended for use in all automobiles requiring an ethylene glycol based product.

## **Applications / Benefits**

- γ Compatible with most commercial antifreeze fluids
- Y Prevents freezing over of automobile cooling systems up to -45°C
- Y Protects most metals in cooling systems
- γ Provides excellent heat rejecting properties

## **Typical Characteristics**

Test Description	Method	Unit		
Specific Gravity @ 15 °C	ASTM D 4052	g/ml	1.049	1.075
Boiling Range	-	°C	105	108
Freezing Point	ASTM D 1177	°C	-15	-35
Appearance	-	-	Pink	Pink

Reference No. 9925AFREEZEPINKREV1 Last revised date: 06-06-24

www.hpure-lube.com

Issued by HPURE Lubricants Tel:(65) 6861 1157

Furnishing the information contained herein does not constitute a representation by HPURE Lubricants that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any third party. HPURE Lubricants assumes no liability for any infringement which might arise out the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrantied of MERCHANTABILTY and FITNESS. Ver.16/1