

## **HPURE GLYCOL COOLANT**

## **Product Description**

Coolant formulated with premium quality, single-phase, ethylene glycol based product. This product provides excellent heat rejecting aluminum protection for all automotive and light duty diesel applications. It also provides outstanding protection for heavy-duty diesel applications when combined with supplemental coolant additives. It protects all commons cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This formulation is compatible with all other major brands of coolant and will not affect automotive hoses and gaskets.

This oil is recommended for automotive and trucks cooling systems. It contains an effective defoamer to prevent foaming in the cooling system for the life of coolant.

It is recommended for use in all automobiles requiring ethylene glycol based coolant.

## **Applications / Benefits**

- Y High quality coolant designed for use in all types of radiator cooling systems.
- y Provides excellent heat rejecting properties
- Y Protects cooling systems under high temperature conditions
- $\gamma$  Be used directly without water dilution

## **Typical Characteristics**

Test Description	Method	Unit	
Density @ 15 °C Freezing Point Boiling Point Appearance	ASTM D 4052 ASTM D 1177 ASTM D 1120 Visual	kg/L °C	1.0140 -6 102 Green

Reference No. 9925COOL-6REV0 Last revised date: 15/1/2024

Issued by HPURE Lubricants Tel:(65) 6861 1157 www.hpure-lube.com Furnishing the information contained herein does not constitute a representation by HPURE Lubricants that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any third party. HPURE Lubricants assumes no liability for any infringement which might arise out the product. The information and suggestions for use and application presented herein represent best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrantied of MERCHANTABILTY and FITNESS. Ver.16/1